



## 8-Position Compression Connectors

### Description

A new series of one-piece compression connectors has emerged as an alternative to two-piece board-to-board connectors. These connectors can be soldered onto a flex circuit or a printed circuit board. They are most suitable for low cost, low profile assembly of board-to-board or board-to-flex electronic devices.

These connectors come with 1.25 mm pitch, with an option of locating post to allow precise alignment on blind mated boards. Upon request, they may be expanded to the preferred contact positions.



### Features & Benefits

- One piece connector on 1.25 mm (.049") and 4.15 mm (.163") centerlines
- 8-position (expandable to other positions)
- SMT solder tail
- High temperature plastic compatible with IR and vapor-phase soldering processes
- Contacts compress directly to solder pads on mating PCB
- Locating post option allows blind mating of board to connector
- Mated working height of 2.9 mm
- One-piece design reduces final assembly cost of product
- Designed for cost-effective, full automation
- Suitable for low-profile assembly

### Target Markets

- Storage
- Mobile phone
- Consumer

### Target Applications

- Read-write application in hard disk drives
- Board-to-board applications in portable electronic devices


### Technical Data

#### Materials

- Housing
  - High temperature plastic (UL 94 V-0)
  - Black Color
  - Applicable solder processes (IR, vapor-phase)
- Contact
  - Terminal (Copper alloy)
- Plating
  - Terminal (Tin lead over Nickel underplate)

For more information, please visit our website at [www.fciconnect.com](http://www.fciconnect.com)

Americas Tel.: 1 800 237 2374 / 1 717 938 7200 Europe Tel.: 33 1 3949 2183 Asia Pacific Tel.: 65 6549 6666



### Mechanical Performance

- Contact retention force
  - Terminal (145 gms min.)
- Durability
  - 25 cycles
- Contact normal force
  - 100 gms min.
- Mated working height
  - 2.9 mm

### Electrical Performance

- Insulation resistance
  - 100 M $\Omega$  min.
- Withstanding voltage
  - 500V ac
- Current rating
  - Terminal (1.8 amp continuous)
- Contact resistance
  - $\Delta R = 20$  m $\Omega$  max.

### Approvals and Certifications

- UL and CSA pending

### Packaging

- Tube
- Tape-and-Reel


### Ordering Information

- Part Number
  - 10014599

### Applications



Connector on a Flex Circuit



Connectors on a Printed Circuit Board

© Copyright FCI, S.A.  
All rights reserved.

SF 08PCC 0403 E

For more information, please visit our website at [www.fciconnect.com](http://www.fciconnect.com)  
Americas Tel.: 1 800 237 2374 / 1 717 938 7200 Europe Tel.: 33 1 3949 2183 Asia Pacific Tel.: 65 6549 6666